



US009397605B2

(12) **United States Patent**
Stapleton

(10) **Patent No.:** **US 9,397,605 B2**
(45) **Date of Patent:** **Jul. 19, 2016**

(54) **PANEL MOUNTING BRACKET WITH
UNDER-MOUNTING CLAMP AND RELATED
METHODS**

(71) Applicant: **Kevin Stapleton**, San Antonio, TX (US)

(72) Inventor: **Kevin Stapleton**, San Antonio, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/528,399**

(22) Filed: **Oct. 30, 2014**

(65) **Prior Publication Data**

US 2015/0113889 A1 Apr. 30, 2015

Related U.S. Application Data

(60) Provisional application No. 61/897,473, filed on Oct. 30, 2013.

(51) **Int. Cl.**
H02S 20/22 (2014.01)
H02S 20/23 (2014.01)
F24J 2/52 (2006.01)

(52) **U.S. Cl.**
CPC **H02S 20/22** (2014.12); **F24J 2/5245**
(2013.01); **F24J 2/5254** (2013.01); **H02S 20/23**
(2014.12); **F24J 2002/5218** (2013.01); **Y02B**
10/12 (2013.01); **Y02B 10/20** (2013.01); **Y02E**
10/47 (2013.01)

(58) **Field of Classification Search**
CPC H02S 20/22; E04B 1/40; E04B 2001/405;
F24J 2/5245; F24J 2/5254; F24J 2002/5218;
Y02B 10/20; Y02B 10/12; Y02E 10/47
USPC 52/173.3
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,121,583 A * 6/1992 Hirai F24J 2/045
52/173.3
5,367,843 A * 11/1994 Hirai F24J 2/05
126/621
5,497,587 A * 3/1996 Hirai F24J 2/045
136/251
5,571,338 A * 11/1996 Kadonome E04D 3/3608
136/251
6,105,317 A * 8/2000 Tomiuchi E04D 3/08
52/173.3
7,434,362 B2 * 10/2008 Liebendorfer F24J 2/5205
136/244
7,956,280 B2 * 6/2011 Kobayashi F24J 2/5211
126/704
7,963,074 B2 6/2011 Schwarze et al.
8,181,402 B2 * 5/2012 Tsuzuki F24J 2/045
126/621
2002/0035811 A1 * 3/2002 Heuel E04D 13/10
52/506.05

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 14/279,799, filed May 16, 2014.


Primary Examiner — James Ference

(74) *Attorney, Agent, or Firm* — Allen, Dyer, Doppelt, Milbrath & Gilchrist, P.A.

(57) **ABSTRACT**

A system for mounting a solar panel(s) on a building, where the solar panel has an outer frame defining a lip. The system may include a plurality of panel mounting brackets each including a base to be positioned on the building, and a vertical extension having a proximal end coupled to the base and a distal end vertically spaced apart from the base, with the distal end defining a fastener channel therein. The system may also include a plurality of mounting clamps each including a bottom flange, and a top flange spaced apart from the bottom flange and partially overhanging the bottom flange and defining a slot therebetween to receive the lip. An end extension may couple respective ends of the bottom flange and top flange together, and a fastener channel connector may be coupled to the bottom flange and configured to be slidably received within the fastener channel.

11 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0070368	A1 *	4/2003	Shingleton	F24J 2/5205 52/173.3	2010/0288338	A1 *	11/2010	Yamamoto	F24J 2/4614 136/251
2003/0101662	A1 *	6/2003	Ullman	E04D 13/12 52/27	2011/0047903	A1 *	3/2011	Kobayashi	F24J 2/5211 52/173.3
2007/0295391	A1 *	12/2007	Lenox	F24J 2/5207 136/251	2011/0070765	A1 *	3/2011	Kobayashi	F24J 2/5207 439/387
2008/0053517	A1 *	3/2008	Plaisted	F24J 2/5207 136/251	2011/0120529	A1 *	5/2011	Nakamura	H01L 31/048 136/251
2008/0066801	A1 *	3/2008	Schwarze	F24J 2/5241 136/251	2011/0138585	A1 *	6/2011	Kmita	F24J 2/5258 24/522
2008/0169018	A1 *	7/2008	Miyamoto	F24J 2/5207 136/251	2011/0154750	A1 *	6/2011	Welter	F24J 2/045 52/173.3
2009/0165843	A1 *	7/2009	Horioka	F24J 2/4612 136/251	2011/0214365	A1 *	9/2011	Aftanas	F24J 2/5258 52/173.3
2010/0154784	A1 *	6/2010	King	F24J 2/464 126/623	2011/0220596	A1 *	9/2011	Cusson	F24J 2/5207 211/41.1
2010/0236183	A1 *	9/2010	Cusson	F24J 2/5207 52/645	2011/0239546	A1 *	10/2011	Tsuzuki	F24J 2/4614 52/11
2010/0243035	A1 *	9/2010	Nakamura	F24J 2/5211 136/251	2011/0314752	A1 *	12/2011	Meier	F24J 2/5211 52/173.3
2010/0276558	A1 *	11/2010	Faust	F24J 2/5205 248/222.14	2012/0244729	A1 *	9/2012	Rivera	F24J 2/4638 439/97
					2013/0048056	A1 *	2/2013	Kilgore	F24J 2/5256 136/251
					2014/0109496	A1	4/2014	Stapleton	

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

1

PANEL MOUNTING BRACKET WITH UNDER-MOUNTING CLAMP AND RELATED METHODS

TECHNICAL FIELD

The present disclosure generally relates to mounting fixtures, and, more particularly, to mounting fixtures or brackets for rooftop panel installations, such as for solar panels, for example.

BACKGROUND

Solar panels, such as photovoltaic (PV) and solar water heating panels, are frequently used to take advantage of electrical power generation and heating properties of sunlight. To provide space savings and potentially enhanced efficiency, solar panels are in many cases installed on rooftops of buildings (e.g., office buildings, houses, etc.). However, because of winds and storms, the mounting fixtures used for installing solar panels on buildings need to be sufficiently strong and durable to reduce the chances of damage or injury from a panel coming loose during a storm, etc.

Various mounting fixtures have been developed for solar panel installation. For example, U.S. Pat. No. 7,963,074 discloses a device for fixing a photovoltaic module on a sloping roof having a roof structure and a roof covering with individual roof covering elements. The device includes a roof-side connecting piece disposable beneath the roof covering and a module-side connecting piece disposable on an edge of the photovoltaic module. A flexible retaining element interconnects the roof-side connecting piece and the module-side connecting piece. The flexible retaining element is loadable by pulling and adapted to be guided through the roof covering without altering a position or shape of the individual roof covering elements.

Despite the existence of such mounting fixtures, further enhancements may be desirable in some applications.

SUMMARY

A system for mounting at least one solar panel on a building is provided, where the solar panel has an outer frame defining a lip. The system may include a plurality of panel mounting brackets each including a base to be positioned on the building, and a vertical extension having a proximal end coupled to the base and a distal end vertically spaced apart from the base, the distal end defining a fastener channel therein. The system may also include a plurality of mounting clamps each including a bottom flange, a top flange spaced apart from the bottom flange and partially overhanging the bottom flange and defining a slot therebetween to receive the lip of the at least one solar panel, an end extension coupling respective ends of the bottom flange and top flange together, and a fastener channel connector coupled to the bottom flange and configured to be slidably received within the fastener channel.

More particularly, the fastener channel connector may comprise a T-shaped connector coupled to the bottom flange on a side thereof opposite the top flange and configured to be slidably received within the fastener channel. In accordance with another example embodiment, the fastener channel connector may include a horizontal member having an upper surface coupled to the bottom flange and a lower surface to be positioned on the distal end of the vertical extension, a pair of spaced apart vertical side members on opposite sides of the horizontal member and configured to extend along the distal

2

end of the vertical extension when the lower surface of the horizontal member is positioned on the distal end of the vertical extension, a bolt coupled to the lower surface of the horizontal member and configured to extend downward into the fastener channel when the lower surface of the horizontal member is positioned on the distal end of the vertical extension, and a nut to be screwed onto the bolt and configured to be slidably received within the fastener channel.

In an example embodiment, the at least one solar panel may comprise a plurality of solar panels, and the fastener channel of each vertical extension may be configured to slidably receive at fastener channel connectors of at least two mounting clamps each coupled to the outer frame of different respective solar panels. Each mounting clamp may further include at least one set screw carried by the bottom flange to secure the lip of the at least one solar panel within the slot.

The vertical extension may be laterally centered on the base, for example. Also by way of example, each panel mounting bracket may comprise aluminum. Furthermore, the base may define a plurality of mounting holes on opposing sides of the vertical extension. In one example embodiment, the vertical extension member may be hollow and may have a plurality of cross-support members therein.

A related solar panel mounting assembly including a panel mounting bracket and a mounting clamp as described briefly above are also provided. Moreover, a method for mounting at least one solar panel on a building using a plurality of the solar panel mounting assemblies is also provided.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an end view of a panel mounting bracket in accordance with an exemplary embodiment of the invention including an under-mounting clamp.

FIG. 2 is a top view of the mounting bracket of FIG. 1 with mounting holes for securing the bracket to a structure.

FIG. 3 is a side view of the mounting bracket with a single mounting clamp for attaching to the exterior sides of panels located at the perimeter of a panel array.

FIG. 4 is a side view of a mounting bracket attached to the frame of the underside of a panel at the perimeter of a panel array.

FIG. 5 is a side view of a mounting bracket with two mounting clamps for attaching to respective frames of two adjacent modules.

FIG. 6 is an end view of a mounting bracket with two mounting clamps respectively connected to two adjacent modules.

FIG. 7 is a three-dimensional perspective view of a pair of mounting brackets as shown in FIG. 4 each having a respective mounting clamp coupled to a same panel.

FIG. 8 is a top view of two panels as they would appear installed on a rooftop using a plurality of the bracket assemblies illustrated in FIGS. 4 and 6.

FIGS. 9-11 are respective side, end, and perspective illustrations of another example mounting bracket assembly which includes another example fastener channel connector configuration.

DETAILED DESCRIPTION

The present description is made with reference to the accompanying drawings, in which exemplary embodiments are shown. However, many different embodiments may be used, and thus the description should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be

thorough and complete. Like numbers refer to like elements throughout, and prime notation is used to indicate similar elements in different embodiments.

Referring initially to FIGS. 1-8, an assembly 30 for mounting one or more solar panels 31 on a building (e.g., on a roof) is first described. The assembly 30 illustratively includes a mounting bracket 32 (which is also referred to as a “foot” herein) for installing solar panels or modules 31. By way of background, solar modules or panels are typically mounted to racking using clamps that grip the module and hold it tight to rails which are mounted to rooftops by “L” shaped feet. The foot 32 illustrated in FIG. 1 advantageously avoids the need for such rails and clamps by mounting panels to roofs through the use of multiple feet (e.g., four feet, although other numbers of feet may be used), which are attached to the underside of each panel. More particularly, each panel 31 may include an outer frame 33 defining a lip 34 on the underside thereof, and in the example embodiment illustrated in FIGS. 7 and 8 the outer frame carries a photovoltaic cell array 35 therein (although the assembly 30 may also be used for mounting solar hot water heating panels as well, for example).

In the illustrated example, the foot 32 has a generally rectangular-shaped central vertical extension portion 36 with one or more hollow central area(s) or channel(s) 37 therethrough. A proximal end 38 of the vertical extension 36 is coupled to a flange or base 39 of the foot 32, and a distal end 40 of the vertical extension is vertically spaced apart from the proximal end, as seen in FIG. 1. An upper fastener channel slot or groove 41 is defined in the distal end 40 (see FIG. 2), though grooves may instead or in addition be provided on either or both sides of the vertical extension 36 in some embodiments, if desired. The foot 32 has a height h and a width w, which in an example embodiment may both be three inches, but other dimensions may also be used in different embodiments.

The base 39 illustratively includes two side extensions 42, 43 that extend outwardly away from the vertical extension 36 so that the vertical extension is centered on the base (although it need not be centered in all embodiments). Thus, when the bottom surface of the base 39 sits flat on a rooftop or roof deck 44 upon installation, the vertical extension 36 points upward or normal to the surface of the roof (although the vertical extension may form different angles with respect to the base besides 90° in different embodiments). Serrations or other surface features may optionally be included on portions of the upper surface of the distal end 40 and/or the bottom surface of the base 39, if desired. The serrations may advantageously provide for improved electrical grounding with the frame of the panel, as well as increased grip or friction, for example, as will be appreciated by those skilled in the art.

In the illustrated example, the feet 32 are attached to the underside lip 34 of each panel frame 33, as shown in FIGS. 4 and 7. While still on the ground, the installation technician may advantageously attach the feet 32 to the bottom of each panel on their longer sides (e.g., top and bottom sides) with the front edge of the foot facing out from the panel using an under-mounting clamp 50. However, the feet 32 may be attached to the other sides of the panels 31 as well in some embodiments, and the panels may also be attached to the feet after the feet have been installed on the rooftop 44, if desired.

The mounting clamp 50 illustratively includes a bottom flange 51, a top flange 52 spaced apart from the bottom flange and partially overhanging the bottom flange (see FIG. 3) to define a slot therebetween, and an end extension 53 coupling respective ends of the bottom flange and top flange together. The slot is configured to engage or receive the lip 34 of the solar panel 31, as seen in FIG. 7. The mounting clamp 50

further illustratively includes a fastener channel connector 54 coupled to the bottom flange 51 and configured to be slidably received within the fastener channel 41.

In the present example, the fastener channel connector 54 illustratively includes a T-shaped connector or slide bar coupled to the bottom flange 51 on a side thereof opposite the top flange 52 (i.e., on its bottom side). The T-shaped connector 57 is configured to be slidably received within the fastener channel 41, as seen in FIGS. 1 and 2. The fastener channel connector 54 may first be attached to the solar panel 31, and then the feet 32 connected to respective mounting clamps 50. Another approach is that the mounting clamps 50 may be coupled to respective feet 32, and the entire assembly 30 (i.e., mounting clamp plus foot) may then be connected to the solar panel 31. The mounting clamp 50 further illustratively includes a retaining set screw(s) 55 which may be tightened to secure the lip 34 within the slot between the bottom and top flanges 51, 52, and a slide bar retaining bolt 58 and a corresponding nut 59.

A first row of panels 31 may then be attached on the roof 44 with deck screws 60 through mounting holes 61 in the side extensions 42, 43 on the outward or perimeter side of the array, typically in a straight line. In some instances, a sealant may be used under each foot 32, if desired. Various types of sealant may be used, such as caulking, tar, Butyl tape, etc. An adjacent row of solar panels 31 may then be attached with additional feet 32 adjacent to the first row of solar panels so as to share the second set of feet (see FIGS. 5 and 6) between them. That is, the fastener channel 41 of each vertical extension portion may be of sufficient dimensions or length to slidably receive two (or more) fastener channel connectors 54 therein. While the feet 32 are shared between adjacent panels, the mounting clamps 50 retain each solar panel 31 independently. This allows each solar panel 31 to be installed and secured individually, and in the event that a solar panel is to be removed from an array, this can be done independently without loosening the adjacent solar panel, which is generally not possible with typical panel or panel mounting arrangements.

The installation process may be repeated for each row of solar panels 31 to be installed, until the last row of solar panels is reached. On the outer perimeter of the last solar panel 31, one mounting clamp 50 may be used per foot 32 to attach to the outer edge of each of the perimeter solar panels (see, e.g., FIGS. 4 and 7).

A significant advantage of the assembly 30 is that it may advantageously be connected or coupled to a respective solar panel 31 on the ground, rather than having to be coupled to the solar panel on the roof 44 where this is more difficult (and potentially more dangerous), and where it is much harder to recover dropped tools, screws, nuts, washers, or other parts. Moreover, this may also help expedite the installation process.

The hollow channels or passageways 37 in the vertical extension 36 may serve as wire management channels, which may be used for keeping electrical transmission wires (e.g., for PV panels) or temperature sensor wires (e.g., for a water heater panels) secured in place. However, the cross-support members 56 which define the channels 37 need not be included in all embodiments, although even when the channels are not used for routing wires the cross-support members may provide added rigidity and/or stability to the feet 32. It should also be noted that the vertical extension 36 of the foot 32 need not be hollow in all embodiments, and that different shapes beside a rectangular shape may also be used for the base 39 and/or the vertical extension in some embodiments. Example materials for the foot 32 and the mounting clamp 50 may include aluminum, which may be extruded into the

5

desired shape, although other suitable materials may also be used in different embodiments. The various screws and fasteners described herein may be stainless steel, brass, galvanized steel, etc.

Here again, a sealant may optionally be used under each foot **32** so that the screws **60** are screwed through the foot **32** and sealant into the roof or decking **44** at desired locations. By way of example, two or more feet **32** may be secured to the roof **44** to receive one side of the panel, i.e., two (or more) feet are used on each of the top and bottom sides or edges of the solar panel **31**, as shown in FIG. 7, although in some embodiments a single foot may be used.

It should be noted that the above-described mounting assembly **30** may be used with a variety of roof types, including flat and sloped roofs, and over different types of roof coverings (e.g., shingles, tiles, panels, etc.). Moreover, the mounting feet may be used for installations other than on rooftops, such as where mounting to the side of a building or other structure is required.

In accordance with another example embodiment now described with reference to FIGS. 9-11, the fastener channel connector **54'** may in this configuration include a horizontal base or platform member **70'** having an upper surface coupled to the mounting clamp **50'** and a lower surface positioned on the distal end **40'** of the vertical extension **36'**, instead of the slide bar configuration shown in FIG. 1. A pair of spaced apart vertical side members **71'** are coupled to opposite sides of the horizontal member **70'** and extend along the distal end **40'** of the vertical extension **36'** when the lower surface of the horizontal member is positioned on the distal end of the vertical extension **36'**. Stated alternatively, this configuration generally has an inverted "U" shape (as seen from the end view of FIG. 10) defining a channel that fits on the distal end **40'** of the vertical extension **36'**. A bolt **72'** is coupled to the horizontal member **70'** and configured to extend downward into the fastener channel **41'** when the lower surface of the horizontal member is positioned on the distal end **40'** of the vertical extension **36'**, and a nut **73'** may be screwed onto the bolt and configured to be slidably received within the fastener channel.

In the present example, the fastener channel connector **54'** allows for the mounting clamp **50'** of each independent solar panel to remain attached to that solar panel, but yet be removed from the corresponding mounting bracket **32'**, allowing each solar panel to be detached from its mounts by removing each retaining bolt **72'** and nut **73'**. This facilitates the removal of solar panels independent from other panels within the array without the disruption of adjacent panels, which again may not be possible with typical mounting systems.

In another example embodiment, the above-described assembly **30** may be used for mounting solar panels without an outer frame (i.e., a frameless panel or module). That is, the mounting clamps **50** could be coupled directly to the photovoltaic cell array **35**, by directing the slot between the bottom and top flanges **51**, **52** inward to receive the cell array panel therein (as opposed to the slots facing outward to receive the outer frame lip **34** as described above). To this end, a material such as rubber, etc., may be positioned or adhered within the slot to help protect and/or securely hold the cell array **35**. Moreover, the set screw **55** may still be used to secure the cell array **35** within the slot, and in some configurations a small plate (e.g., stainless steel plate, etc.) may be coupled to or actuated by the set screw to be pressed into contact to secure the cell array within the slot, as will be appreciated by those skilled in the art. This may be beneficial to help keep the glass substrate upon which the cell array **35** is formed from cracking, for example.

6

Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented herein. Therefore, it is understood that the invention is not to be limited to the specific exemplary embodiments disclosed herein.

That which is claimed is:

1. A system for mounting a plurality of solar panels on a building, each one of the plurality of solar panels comprising an outer frame defining a lip, the system comprising:

a plurality of panel mounting brackets each comprising:
a base to be positioned on the building, and
a vertical extension having a proximal end coupled to the base and a distal end vertically spaced apart from the base, the distal end defining a fastener channel therein; and

a plurality of mounting clamps each comprising:
a bottom flange having first and second ends,
a top flange having first and second ends, the top flange spaced apart from the bottom flange and partially overhanging the bottom flange and defining a slot therebetween to receive the lip of a respective one of the plurality of solar panels,
an end extension coupling the first ends of the bottom flange and the top flange together, and
a fastener channel connector coupled to the bottom flange and configured to be slidably received within the fastener channel of a respective vertical extension; wherein the fastener channel of the vertical extension of each one of the plurality of panel mounting brackets is configured to slidably receive the fastener channel connectors of at least two of the plurality of mounting clamps each coupled to the lip of different respective solar panels.

2. The system of claim 1 wherein the fastener channel connector comprises a T-shaped connector coupled to the bottom flange on a side thereof opposite the top flange and configured to be slidably received within the fastener channel.

3. The system of claim 2 wherein each one of the plurality of mounting clamps further comprises a retaining bolt and corresponding nut coupling the T-shaped connector to the bottom flange.

4. The system of claim 1 wherein each of the plurality of mounting clamps further comprises at least one set screw securing the bottom flange to the lip of the respective solar panel within the slot.

5. The system of claim 1 wherein the vertical extension is laterally centered on the base.

6. The system of claim 1 wherein each one of the plurality of panel mounting brackets comprises aluminum.

7. The system of claim 1 wherein the base defines a plurality of mounting holes on opposing sides of the vertical extension.

8. The system of claim 1 wherein the vertical extension is hollow and comprises at least one cross-support member therein.

9. A mounting assembly for at least one solar panel comprising:

a panel mounting bracket comprising:
a base to be positioned on a building, and
a vertical extension having a proximal end coupled to the base and a distal end vertically spaced apart from the base, the distal end defining a fastener channel therein; and

a mounting clamp comprising:
a bottom flange having first and second ends,
a top flange having first and second ends, the top flange spaced apart from the bottom flange and partially

overhanging the bottom flange and defining a slot therebetween to receive the lip of the at least one solar panel,

an end extension coupling the first ends of the bottom flange and the top flange together, and

a fastener channel connector coupled to the bottom flange and configured to be slidably received within the fastener channel of a respective vertical extension, the fastener channel connector comprising:

a horizontal member having an upper surface coupled to the bottom flange and a lower surface to be positioned on the distal end of the vertical extension,

a pair of spaced apart vertical side members on opposite sides of the horizontal member and configured to extend along the distal end of the vertical extension when the lower surface of the horizontal member is positioned on the distal end of the vertical extension,

a bolt coupled to the lower surface of the horizontal member and configured to extend downward into the fastener channel when the lower surface of the horizontal member is positioned on the distal end of the vertical extension, and

a nut to be screwed onto the bolt and configured to be slidably received within the fastener channel.

10. The assembly of claim **9** further comprising at least one set screw securing the bottom flange of the mounting clamp to the panel mounting bracket.

11. The assembly of claim **9** further comprising at least one set screw securing the top flange to the lip of the at least one solar panel within the slot.

* * * * *